

## Safe-R

Superior Performance  
Phenolic Insulation

## SR/CW

Insulation for  
Partial Fill Cavity Walls

The partial fill cavity wall insulation shall be Xtratherm Safe-R SR/CW \_\_\_mm manufactured to EN 13166 by Xtratherm, comprising a rigid Phenolic core between low emissivity foil facings. The SR/CW \_\_\_mm with Agrément declared Lambda value as low as 0.020W/mK to achieve a U value of \_\_\_W/m<sup>2</sup>K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 150, F30 12

### Insulation

Phenolic Rigid Foam

### Standard

BS EN 13166

### Certification

BBA Certification No. 10/4803. Issue date: 14 December 2010  
BS EN ISO 9001 Quality Management System  
BS EN ISO 14001 Environmental Management System

### Manufacturer

#### Xtratherm UK Limited

Holmewood Industrial Park, Holmewood  
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

[info@xtratherm.com](mailto:info@xtratherm.com)

[www.xtratherm.com](http://www.xtratherm.com)

### Face size

1200 x 450 mm

### Edge profile

Straight Edge

### Thickness

50 mm / 60 mm / 75 mm / 80mm / 100mm

### Product reference

Xtratherm Safe-R SR/CW  
Partial Fill Cavity Wall Insulation

Other sizes available dependent on quantity & lead time.