

Thin-R

PIR Insulation

TR/ALU

Insulation for
Single Ply Mechanically Fixed Systems

The tapered roof insulation shall be Xtratherm Thin-R TR-ALU manufactured to EN 13165 by Xtratherm, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings. The TR-ALU ___mm with a Agrément declared Lambda value of 0.022 W/mK to achieve a U value of ___W/m²K for the roof element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause J42 420, J42 10

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BBA Certification No. 11/4817. Issue date: 28 February 2011
BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Xtratherm Limited

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.ie

www.xtratherm.ie

Face size

1200 x 1200 mm

Edge Profile

Straight Edge

Thickness

30-50mm / 50-70mm / 70-90mm /
90-110mm

Product reference

Xtratherm Thin-R TR-ALU Tapered
Roof Insulation.

Other tapers available dependent on quantity & lead time.