

Thin-R

PIR Insulation

XT/CW (T&G)

Insulation for
Partial Fill Cavity Wall

The partial fill cavity wall insulation shall be Xtratherm Thin-R XT/CW T&G manufactured to EN 13165 by Xtratherm, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings. The XT/CW T&G ___mm with a Agrément declared Lambda value of 0.022 W/mK to achieve a U value of ___W/m2K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 155, F30 12

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BBA Certification No. 08/4613 Issue date: 5 August 2011
BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY.

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Xtratherm Limited

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.ie

www.xtratherm.ie

Face size

1200 x 450 mm

Edge Profile

T&G all four edges

Thickness

40 mm / 50 mm / 60 mm / 70 mm /
80mm / 100mm

Product reference

Xtratherm Thin-R XT/CW T&G Partial Fill
Cavity Wall Insulation

Other sizes available dependent on quantity & lead time.