

Thin-R

PIR Insulation

XT/TF

Insulation for Timber Frame Systems

The wall insulation shall be Xtratherm Thin-R XT/TF manufactured to EN 13165 by Xtratherm, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings. The XT/TF_ _ _mm with a Agrément declared Lambda value of 0.022 W/mK to achieve a U value of _ _ _W/m²K for the timber frame wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 155, K10 15, K10 205, F30 12, K10 245, K10 25, P10 180, P10 40

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BBA Certification No. 08/4613. Issue date: 5 August 2011
BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Xtratherm Limited

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.ie

www.xtratherm.ie

Face size

2400 x 1200mm

EdgeProfile

Straight Edge

Thickness

20mm / 25mm / 30mm / 35mm / 40mm /
45mm / 45mm / 50mm / 55mm / 60mm /
65mm / 70mm / 75mm / 80mm / 90mm /
100mm / 140mm

Product reference

Xtratherm Thin-R XT/TF Timber
Frame Insulation

Other sizes available dependent on quantity & lead time.