

Thin-R

PIR Insulation

XT/TL

Insulation for Dry Lining
Plasterboard DAB/Adhesive Fixing

The insulated dry lining wall insulation shall be Xtratherm Thin-R XT/TL manufactured to EN 13165 by Xtratherm, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings. The XT/TL__mm with a Agrément certified Lambda value of 0.022 W/mK (PIR only) bonded to 12.5mm plasterboard, to achieve a U value of __ W/m²K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause K10 205

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BBA Certification No. 04/4130.
BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System
BS OHSAS 18001 Health and Safety Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Xtratherm Limited

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.ie

www.xtratherm.ie

Face size

UK: 2400 x 1200 mm

IRL: 2438 x 1200 mm

Edge Profile

Plasterboard – Tapered

PIR – Square Edge

Thickness

UK: 25mm / 30mm / 40mm / 50mm /
60mm / 70mm

IRL: 17mm / 25mm / 38mm / 50mm /
60mm / 70mm

Product reference

Xtratherm Thin-R XT/TL, Thermal
Liner Insulation

Other sizes available dependent on quantity & lead time.