

Safe-R

Superior Performance
Phenolic Insulation

SR/STP

Insulation for
Soffit Application (Soffit Plus)

The soffit insulation shall be Xtratherm Safe-R SR/STP __ __mm manufactured to EN 13166 by Xtratherm, comprising a rigid Phenolic core between low emissivity foil facings bonded to 6mm building panel. The SR/ST __mm with Lambda value as low as 0.020 W/mK (Phenolic only) to achieve a U value of __W/m²K for the soffit element to be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause P10 185, P10 217

Insulation

Phenolic Rigid Foam

Standard

BS EN 13166

Certification

BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Face size

2400 x 1200 mm

Edge profile

Straight Edge

Thickness

80mm / 100mm

Product reference

Xtratherm Safe-R SR/STP
Soffit Insulation

Other sizes available dependent on quantity & lead time.