

## Safe-R

Superior Performance  
Phenolic Insulation

## SR/TB

Insulation for  
Dry Lining Plasterboard Mechanical Fixing

The insulated drylining wall insulation shall be Xtratherm Safe-R SR/TB manufactured to EN 13950 by Xtratherm, comprising a rigid Phenolic core between composite glass tissue/foil facings. The SR/TB\_ \_ \_mm with Lambda value as low as 0.020 W/mK (Phenolic only), bonded to 12.5mm plasterboard, to achieve a U value of \_ \_ \_W/m<sup>2</sup>K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause K10 205, K10 15

### Insulation

Phenolic Rigid Foam

### Standard

BS EN 13950

### Certification

BS EN ISO 9001 Quality Management System  
BS EN ISO 14001 Environmental Management System

### Manufacturer

#### Xtratherm UK Limited

Holmewood Industrial Park, Holmewood  
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

[info@xtratherm.com](mailto:info@xtratherm.com)

[www.xtratherm.com](http://www.xtratherm.com)

### Face size

2400 x 1200 mm

### Thickness

25mm / 40mm / 50mm / 60mm / 75mm /  
80mm / 100mm

### Edge profile

Plasterboard - Tapered  
Phenolic - Square Edge

### Product reference

Xtratherm Safe-R SR/TB  
Thermal Liner Insulation

Other sizes available dependent on quantity & lead time.